



## Comparative Study on Face Image Segmentation Using Various Edge Detection Techniques

**Dr. S. Pannirselvam**

Research Supervisor & Head  
Department of Computer Science  
Erode Arts & Science College (Autonomous)  
Erode -9, Tamilnadu, India

**S.Prasath\***

Ph.D. Research Scholar  
Department of Computer Science  
Erode Arts & Science College (Autonomous)  
Erode -9, Tamilnadu, India

---

**Abstract**— *Image Segmentation plays an important role in image processing and computer vision. Segmentation subdivides an image into its constituent regions or object. Image segmentation can be obtained by using various methods, some which are easier to achieve than others due to the need of high programming. Edge detection techniques are mostly used to find object based on local changes in intensity field of image processing applications. In this paper attempt to study the most commonly used edge detection techniques such as canny, Sobel, Prewitt, Roberts, LoG. From the experiments and results observed the canny edge detection gives better results.*

**Keywords**— *PCA, ICA, LDA, DCT, LFA, LoG.*

---

### I. INTRODUCTION

Since last decades, researchers are involved on face recognition in image processing and they achieved so many mile stone because face recognition is the critical stage to identify the face in images due to pose, presence or absence of structural components, facial expression, occlusion, image orientation. Several methods have been evolved to increase recognition rate. Many face recognition methods have been proposed. Basically, they techniques can be classified into three categories [1]: Holistic or Global-Appearance-based methods [2], Local-feature-based methods or local appearance-based methods, and hybrid methods [3]. In Global-Appearance-based methods, the whole image is used as a raw input to the learning process. Examples of these techniques are Principal Component Analysis (PCA), Discrete Cosine Transforms (DCT), and Linear Discriminate Analysis (LDA). The local appearance-based methods can be divided into two groups: The ones that require the use of specific regions located on a face such as eyes, nose and mouth, as well as their relationships with each other [4] and the ones that simply partition the input face image into blocks without considering any specific regions [5]. In hybrid methods, associate feature of the holistic and local techniques. Modular Eigen faces [6] Hybrid Local Feature Analysis (LFA) [7] and Component-based 3D Models [8] are examples of these methods. The most successful and well-studied techniques to face recognition are the appearance-based methods.

While capturing the image, due to motion or interference some disturbance, blur etc is added automatically in the image. This is called noise. The features cannot be extracted correctly from such images. To improve the quality of image, enhancement techniques such as edge sharpening, noise removal etc are used. [9]. The output of image processing can be either an image or a set of characteristics or parameters related to image. The image processing techniques like image restoration, image enhancement, image segmentation. Also, segmentation refers to the process of partitioning a digital image into multiple segments (sets of pixels, also known as super pixels). Image segmentation is typically used to locate objects and boundaries (lines, curves, edges etc.) in images. The segmentation process may include edge detection. Sometimes edge detection is used for feature extraction

### II. EDGE DETECTION TECHNIQUES

#### 2.1 Edge Models

Edge models are classified according to their intensity profiles. A *step* edge involves a transition between two intensity level levels occurring ideally over the distant of 1 pixel. Edges that are blurred and noisy, determined by limitations in the focusing mechanism and noise level determined by the electronic components of imaging system. In such situations, edges are more closely modelled as having an intensity ramp profile. The slope of the ramp is inversely proportional to the degree of blurring in the edge. It can be seen that in this model, there is no thin (1 pixel thick) path. Instead, an edge point which is now any point contained in the ramp, and an edge segment would then be a set of such points that are connected. A third model of an edge is called *roof* edge. Roof edges are models of lines through a region, with the base of a roof edge being determined by the thickness and sharpness of the line [10].

#### 2.2 Sobel Operator

The Sobel edge detection method was introduced by Irwin Sobel in 1970 (Rafael C. Gonzalez (2004)). The Sobel technique of edge detection for image segmentation finds edges using Sobel approximation derivative. Typically it is used to find the approximate absolute gradient magnitude at each point in an input grayscale image. The operator

consist of a pair of 3x3 convolution mask, which is the x and y direction on the image. It is discovered at first derivative level. The horizontal and vertical pixel masks for Sobel Operator are shown in figure 1. This is very similar to Robert Cross operator.

-1	-2	-1
0	0	0
+1	+2	+1

$G_x$

-1	0	+1
-2	0	+2
-1	0	+1

$G_y$

Fig. 2.1 Sobel operator

The mask will be moved until all the images and each value, R, will be kept into an output array, which is located at the mask centre. The formula to find the gradient magnitude is Equation (1).

$$|G| = |G_x| |G_y| \quad \text{Equ (1)}$$

Where  $G_x$  and  $G_y$  are given by the formulae (2) and (3).

$$G_x = (a_2 + ca_3 + a_4) - (a_0 + ca_7 + a_6) \quad \text{Equ (2)}$$

$$G_y = (a_0 + ca_1 + a_2) - (a_6 + ca_5 + a_4) \quad \text{Equ (3)}$$

Where c is a constant with a value 2.

### 2.3 Prewitt Edge Detection

Prewitt Operator is pioneered by Judy Prewitt and is based on the central difference concept and is given by,

$$\frac{\partial p}{\partial x} \approx [p(x+1, y) - p(x-1, y)] / 2 \quad \text{Equ (4)}$$

The convolution masks of prewitt operator are shown in figure 2. Prewitt operator is similar to the Sobel operator and is used for detecting vertical and horizontal edges in images.

-1	0	+1
-1	0	+1
-1	0	+1

Fig. 2.2 Prewitt operator

### 2.4 Robert Cross Edge Detection

The Robert Cross operator performs a simple, quick to compute 2-D spatial gradient measurement on an image. Pixel values at each point in the output represent the estimated absolute magnitude of the spatial gradient of the input image at that point. The operator consists of a pair 2x2 convolution masks as shown in figure 3. This is very similar to the Sobel operator. It uses  $\{+1, -1\}$  operator that will calculate the value

$$p(\bar{x}_i) - p(\bar{x}_j) \quad \text{Equ (5)}$$

For (i,j) pixel at neighbourhood pixel. Mathematically, this equation is known as forward differences.

$$\frac{\partial p}{\partial x} \approx [p(x+1, y) - p(x, y)] \quad \text{Equ (6)}$$

Convolution mask of Robert Cross Operator is shown in Figure 3.

+1	0
0	-1

$g^x$

0	+1
-1	0

$g^y$

Fig. 2.3 Robert Operator

Calculation for gradient magnitude is,

$$G = \sqrt{(g_x \cdot f)^2 + (g_y \cdot f)^2} \quad \text{Equ (7)}$$

### 2.5 Laplacian of Gaussian (LoG)

This edge detector was invented by Marr and Hildreth (1980) who combined Gaussian filtering with the Laplacian. Those who continued his way were Berzins (1984), Shah, Sood and Jain (1986), Huertas and Medioni (1986). The Laplacian is often applied to an image that has first been smoothed with something approximating a Gaussian

Smoothing filter in order to reduce its sensitivity to noise. The operator normally takes a single gray level image as input and produces another gray level image as output. The Laplacian  $L(x,y)$  of an image with pixel intensity values  $I(x,y)$  in Equ (8),

$$L(x, y) = \frac{\partial^2 I}{\partial x^2} + \frac{\partial^2 I}{\partial y^2} \quad \text{Equ (8)}$$

### 2.6 Canny Edge Detection

The current standard edge detection scheme widely used around the world is the canny edge detector. John Canny did for his Masters degree in MIT in 1983. The canny edge detector first smoothes the image, to eliminate noise and then finds the image gradient to highlight regions with high spatial derivatives. The algorithm then tracks along these regions and suppresses any pixel that is not at the maximum. The Canny Edge Detection algorithm consists of the following basic steps [10]:

- Smooth the input image with a Gaussian filter.
- Compute the gradient magnitude of the images.
- Apply non-maxima suppression to the gradient magnitude image.
- Use double thresholding and connectivity analysis to detect and link edges.

### III. EXPERIMENTS AND RESULTS

In this paper, the edge detection technique is used as a preprocessing technique where localization of face is more important. With edge detection techniques, other algorithms can also be used such as Hough Transform, Integro-differential operator etc to localize the face. For our experiments, the sample facial images from the standard facial image database are used. Figure 4 shows the sample images used in our experiments used





Fig.3.1 Output Edge Detected Image

From the below Table 1 it is shows that pixels values of the original image and output of Sobel edge , Roberts edge, Prewitt edge, LoG edge and Canny edge. By considering all the pixels values and the results shows canny edge detected images high compared with other edges.

Table 3.1 Pixels Values of Edge Detected Image

Images	Sobel	Prewitt	Robert	LoG	Canny
1	577	577	588	1294	1813
2	722	719	758	1436	1967
3	586	584	643	1292	1875
4	458	451	557	1054	1852
5	476	479	523	1144	1635

From the below figure 3.2 shows the pictorial representation of the performance evaluated. By analysing the obtained results of the original image and output of Sobel edge, Roberts edge, Prewitt edge, LoG edge and Canny edge. Hence the canny edge detected method for face images is an efficient one.



#### IV. CONCLUSION

The edge detection is the initial step for recognition technique, it is important to show the differences between various edge detection techniques. In this paper we studied the most commonly used edge detection techniques such as Canny, Prewitt, Sobel and Roberts. The Prewitt operator has a major drawback that it is very sensitive to noise and it does not consider the high frequency variation. The Roberts operator works well only when the acquired image has very less noise and well defined edges. The Sobel operator is having smoothing capability, which smoothen all the edges. So it is difficult to find the edges correctly. Canny operator finds all the strong and weak edges those are connected to strong edges only. Therefore, edge features can be extracted easily and correctly with canny operator. Computationally Prewitt, Sobel and Roberts operators are simple whereas Canny is more expensive, even though it provides better results.

#### REFERENCES

- 1) Zhao W. and Chellappa R. 2006. Face processing advanced modeling and methods. Elsevier.
- 2) HeiseleB., Ho P., WuJ., and PoggioT. 2003. Face recognition: component-based versus global approaches, Comput. Vision Image Understand. Vol. 91, No. 1-2, pp. 6–21.
- 3) KimC., Oh J. and Choi C.H. Combined Subspace Method Using Global and Local Features for Face Recognition. Proceedings of International Joint Conference on Neural Networks, Montreal, Canada, 2005.
- 4) Ullman S.,Vidal-Naquet M. and SaliE. 2002. Visual features of intermediate complexity and their use in classification. Nature neuroscience. Vol. 5, No. 7, pp. 682-687.
- 5) Hazim K. and Rainer S.2005. Local Appearance based Face Recognition Using Discrete Cosine Transform. Proceedings of the 13th European Signal Processing Conference (EUSIPCO), Antalya, Turkey.
- 6) Pentland A., MoghaddamB. and Starner T. 1994. View- Based and Modular Eigen spaces for Face Recognition. Proc. IEEE Computer Society Conf. Computer Vision and Pattern Recognition, pp. 84-91.
- 7) PenevP.S. and AtickJ. J. 1996. Local feature analysis: A general statistical theory for object representation. Network: Computation in Neural Systems, vol. 7, No. 3, pp. 477-500.
- 8) Bronstein A.M.,Bronstein M.M., Kimmel R. c 2003. Expression invariant 3D face recognition, in: International Conference on Audio-and Video-Based Person Authentication (AVBPA 2003), LNCS, vol. 2688, pp. 62–70.
- 9) S. Jayaraman,S. Esakkirajan, T.Veerakumar, Digital Image Processing, Tata McGraw Hill publication, 2010.
- 10) Rajesh M. Bodade, Dr. Snajay N. Talbar, Lt. Shailendra K. Ojha, Iris Recognition using Rotational Complex Wavelet Filters: A Novel Apporach,978-1-4244-3397-1/08, 2008 IEEE.
- 11) Rafael C. Gonzalez, Richard E. Woods, Digital Image Processing, Third Edition, Pearson Publication, 2011.
- 12) S. Sridhar, Digital Image Processing, Oxford University Press, 2011.